

**PROPRIETARY NOTE**

THIS SPECIFICATION IS THE PROPERTY OF FANNAL AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF FANNAL AND MUST BE RETURNED TO FANNAL UPON ITS REQUEST



SPEC. NUMBER AM-0700070A	PRODUCT GROUP TFT- LCM	REV. V0	ISSUE DATE 2022-10-8	PAGE 1 OF 28
-----------------------------	---------------------------	------------	-------------------------	-----------------

**FN0700D070A**

**Product Specification Rev.V0**

BUYER	
SUPPLIER	FANNAL Electronics CO., LTD
FG-Code	FN0700D070A

Preliminary Specification

Approval Specification

ITEM	BUYER SIGNATURE	DATE
_____	_____	_____
_____	_____	_____
_____	_____	_____

ITEM	SUPPLIER SIGNATURE	DATE
Prepared	<u>DONG</u>	<u>2022-10-11</u>
Reviewed	<u>XIONG</u>	<u>2022-10-11</u>
Approved	<u>JACK</u>	<u>2022-10-11</u>

**PRODUCT GROUP**

**REV**

**ISSUE DATE**



TFT- LCM PRODUCT

V0

2022-10-11

**SPEC. NUMBER**

AM-0700070A

**SPEC . TITLE**

FN0700D070A Product Specification

**PAGE**

2 OF 28

## REVISION HISTORY

REV.	Page.	DESCRIPTION OF CHANGES	DATE	PREPARED
V0		Initial Release	2022-10-8	JACK

**PRODUCT GROUP**

**REV**

**ISSUE DATE**



TFT- LCM PRODUCT

V0

2022-10-11

**SPEC. NUMBER**

**SPEC. TITLE**

**PAGE**

AM-0700070A

FN0700D070A Product Specification

3 OF 28

## Contents

<b>No.</b>	<b>Items</b>	<b>Page</b>
1.0	General Description	4
2.0	Mechanical Drawing	5
3.0	Absolute Maximum Ratings	6
4.0	Electrical Specifications	7
5.0	Interface Description	9
6.0	Optical Specifications	18
7.0	Reliability Test	20
8.0	Precautions	21
9.0	Packing Information	25
10.0	Visual Inspection Criteria For All Customers	26

PRODUCT GROUP

REV

ISSUE DATE



TFT- LCM PRODUCT

V0

2022-10-11

SPEC. NUMBER

SPEC. TITLE

PAGE

AM-0700070A

FN0700D070A Product Specification

4 OF 28

## 1.0 General Description /一般说明

### 1.1 Application /应用


- Industrial
- Automotive
- Medical
- Outdoor highlight

### 1.2 General Specification /通用技术条件

The followings are general specifications at the FN0700D070A.

Parameter	Specification	Unit
LCD size	7.0 (Diagonal)	inch
Number Of Pixels	800(H)×480(V)	pixels
Pixel Pitch	0.0642(H)×RGBx0.179(V)	mm
Active Area	154.08(H)×85.92(V)	mm
Module Size	164.9(W)×100.0(H)×5.7(D)	mm
Display Mode	Normally White	
Interface	RGB 24bit	
Pixel arrangement	RGB-island	
View Direction	12:00	
Power Consumption	LCD: 0.24(Typ.) @VDD=3.3V Backlight: 1.6(Typ.)@IBL=160mA	W
Weight	157	g
Luminance	400 (TYP.)	cd/m <sup>2</sup>
Driver IC	ILI6122+ILI5960	

# 2.0 Mechanical Drawing /机械制图



### 3.0 ABSOLUTE MAXIMUM RATINGS /绝对最大额定值

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit.

Parameter	Symbol	Min.	Max.	Unit	Remark
Power Voltage	V <sub>CC</sub>	-0.5	5.0	V	
	AVDD	-0.5	15.0	V	
	V <sub>GH</sub>	-0.3	42.0	V	
	V <sub>GL</sub>	-20.0	-0.3	V	
	V <sub>GH-VGL</sub>	-0.3	40.0	V	
Signal Input Voltage	V <sub>in</sub>	-0.5	5.0	V	Note 1
Operating Temperature	T <sub>OP</sub>	-20	+70	°C	
Storage Temperature	T <sub>ST</sub>	-30	+80	°C	
Humidity	RH	--	≤95	%	T <sub>a</sub> ≤40°C
		--	≤85	%	40°C < T <sub>a</sub> ≤50°C
		--	≤55	%	50°C < T <sub>a</sub> ≤60°C
		--	≤36	%	60°C < T <sub>a</sub> ≤70°C
		--	≤24	%	70°C < T <sub>a</sub> ≤80°C
Absolute Humidity	AH	--	≤70	g/m <sup>3</sup>	T <sub>a</sub> > 70°C

Note1: Input voltage include R0~R7, G0~G7, B0~B7, DCLK, HSYNC, VSYNC, DE, R/L, U/D,MODE, RESET,DITHB.

Note2: T<sub>a</sub> means the ambient temperature.

It is necessary to limit the relative humidity to the specified temperature range.  
Condensation on the module is not allowed.

## 4.0 ELECTRICAL SPECIFICATIONS/电气规范

### 4.1 TFT LCM Module

[Ta =25±2 °C]

Parameter	Symbol	Min.	Typ.	Max.	Unit
Digital supply Voltage	Vcc	3.0	3.3	3.6	V
Analog supply Voltage	AVDD	10.1	10.4	10.7	V
Gate on Voltage	VGH	14.4	16.0	17.6	V
Gate off Voltage	VGL	-7.7	-7.0	-6.3	V
Power Supply current	IDD	-	20	-	mA
Input logic high voltage	VIH	0.7Vcc	-	Vcc	V
Input logic low voltage	VIL	0	-	0.3Vcc	V
Current of digital supply voltage	Ivcc	1.0	4.0	10	mA
Current of analog supply voltage	Iavdd	5.0	20.0	50	mA
Current of Gate on voltage	Ivgh	0.05	0.2	1.0	mA
Current of Gate off voltage	Ivgl	0.2	0.5	1.0	mA

### 4.2 Backlight Driving Conditions /背光驱动条件

[Ta =25±2 °C]

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Forward Current Voltage	V <sub>F</sub>	8.1	9.3	10.5	V	Note 1
Forward Current	I <sub>f</sub>	-	160	200	mA	
Backlight Power Consumption	W <sub>bl</sub>	-	1.488	2.1	W	
LED Life Time	-	-	30000	-	Hrs	Note 2

Note1: Under LCM operating, the stable forward current should be inputted. And forward voltage is for reference only.

Note2: Optical performance should be evaluated at Ta=25°C. if LED is driven by high current, high ambient temperature & Humidity condition. The life time of LED will be reduced. Operating life means brightness goes down to 50% initial brightness. Typical operating life time is estimated data.

PRODUCT GROUP

REV

ISSUE DATE



TFT- LCM PRODUCT

V0

2022-10-11

SPEC. NUMBER

SPEC. TITLE


PAGE

AM-0700070A

FN0700D070A Product Specification

8 OF 28

4.3 Block Diagram:



## 5.0 Interface Description/接口说明

Connector Name/Designation	Interface Connector/Interface Card
Type Part Number	FPC 0.5Pitch 50P
Mating Housing Part Number	FH12A-50S-0.5H

### 5.1 Pin assignment for LCM module /模组引脚分配

Pin No.	Symbol	I/O	Description
1-2	VLED+	P	Power for LED Backlight(Anode)
3-4	VLED-	P	Power for LED Backlight(Cathode)
5	GND	P	Power ground
6	NC	-	No connection
7	VCC	P	Power for Digital Circuit
8	MODE	I	DE/SYNC Mode select
9	DE	I	Data Input Enable
10	VSYNC	I	Vertical Sync Input
11	HSYNC	I	Horizontal Sync Input
12	B7	I	Blue data(MSB)
13	B6	I	Blue data
14	B5	I	Blue data
15	B4	I	Blue data
16	B3	I	Blue data
17	B2	I	Blue data
18	B1	I	Blue data
19	B0	I	Blue data
20	G7	I	Green data(MSB)
21	G6	I	Green data
22	G5	I	Green data
23	G4	I	Green data
24	G3	I	Green data
25	G2	I	Green data
26	G1	I	Green data
27	G0	I	Green data
28	R7	I	Red data(MSB)
29	R6	I	Red data

**PRODUCT GROUP**

REV

ISSUE DATE



TFT- LCM PRODUCT

V0

2022-10-11

SPEC. NUMBER

SPEC. TITLE

PAGE

AM-0700070A

FN0700D070A Product Specification

10 OF 28

Pin No.	Symbol	I/O	Description
30	R5	I	Red data
31	R4	I	Red data
32	R3	I	Red data
33	R2	I	Red data
34	R1	I	Red data
35	R0	I	Red data
36	GND	P	Power ground
37	DCLK	I	Sample clock
38	GND	P	Power ground
39	LR	I	Left/Right selection
40	UD	I	Up/Down selection
41	VGH	P	Gate ON Voltage
42	VGL	P	Gate OFF Voltage
43	AVDD	P	Power for Analog Circuit
44	RESET	I	Global reset pin
45-46	NC	-	No connection
47	DITHB	I	Dithering function
48	GND	P	Power ground
49-50	NC	-	No connection

I: input, O: output, P: Power

Note 1: DE/SYNC mode select. Normally pull high.

When select DE mode, MODE=" 1" , VS and HS must pull high.

When select SYNC mode, MODE=" 0" , DE must be grounded.


Note 2: When input 18 bits RGB data, the two low bits of R,G and B data must be grounded.

Note 3: Data shall be latched at the falling edge of DCLK.

Note 4: Selection of scanning mode

Setting of scan control input		Scanning direction
U/D	L/R	
GND	DV <sub>DD</sub>	Up to down, left to right
DV <sub>DD</sub>	GND	Down to up, right to left
GND	GND	Up to down, right to left
DV <sub>DD</sub>	DV <sub>DD</sub>	Down to up, left to right

Note 5: Definition of scanning direction.  
Refer to the figure as below:



Note 6: Global reset pin. Active low to enter reset state. Suggest to connect with an RC reset circuit for stability. Normally pull high.

Note 7: Dithering function enable control, normally pull high.  
When DITHB=" 1" ,Disable internal dithering function,  
When DITHB=" 0" ,Enable internal dithering function,

Note 8: Reserve for LED power input.

PRODUCT GROUP

REV

ISSUE DATE



TFT- LCM PRODUCT

V0

2022-10-11

SPEC. NUMBER

SPEC. TITLE

PAGE

AM-0700070A

FN0700D070A Product Specification


12 OF 28

**5.2 Timing Characteristics**

5.2.1 AC Electrical Characteristics

Item	Symbol	Values			Unit	Remark
		Min	Typ	Max		
HS setup time	Thst	8	10	20	ns	
HS hold time	Thhd	8	120	800	ns	
VS setup time	Tvst	8	10	20	ns	
VS hold time	Tvhd	8	96000	640000	ns	
Data setup time	Tdsu	8	10	20	ns	
Data hole time	Tdhd	8	15	20	ns	
DE setup time	Tesu	8	15	20	ns	
DE hole time	Tehd	8	15	20	ns	
DVdd power On Slew rate	Tpor	1	10	20	ms	From 0 to 90%DVDD
RESET pulse width	Trst	1	2	5	ms	
DCLK cycle time	Tcoh	20	30	40	ns	
DCLK pulse duty	Tcwh	40	50	60	%	

5.2.2 Input Clock and data Timing Diagram



CONFIDENTIAL

# PRODUCT GROUP

REV

ISSUE DATE



TFT- LCM PRODUCT

V0

2022-10-11

SPEC. NUMBER

SPEC. TITLE

PAGE

AM-0700070A

FN0700D070A Product Specification

14 OF 28

## 5.2.3 Timing

Item	Symbol	Values			Unit	Remark
		Min	Typ	Max		
Horizontal Display Area	thd	/	800	/	DCLK	
DCLK Frequency	Fclk	26.4	33.3	46.8	MHz	
One Horizontal Line	Th	862	1056	1200	DCLK	
HS pulse width	thpw	1	6	40	DCLK	Note 1
HS Blanking	Thb	46	46	46	DCLK	Note 2
HS Front Porch	Thfp	16	210	354	DCLK	
Vertical Display Area	Tvd	/	480	/	TH	
VS period time	Tv	510	525	650	TH	
VS Pulse width	Tvpw	1	3	20	TH	Note 2
VS Blanking	tvb	23	23	23	TH	Note 2
VS Front Porch	tvfp	7	22	147	TH	

Note1: HS Blanking has included HS pulse width

Note2: VS Blanking has included VS pulse width

Note: Frame rate 60±5Hz

### 5.2.4 Data Input Format



Figure 3. 1 Horizontal input timing diagram.





Figure 3. 2 Vertical input timing diagram.


**5.5 Power on/off sequence :**

Power On



Symbol	SPEC			Unit
	Min	Typ	Max	
t1	0.5	5.0	20.0	ms
t2	1.0	1.0	1.5	ms
t3	10.0	15.0	20.0	ms
t4	20.	22.0	24.0	ms
t5	1.0	2.0	3.0	ms
t6	5.0	6.0	7.0	ms
t7	1.5	2.0	4.0	ms
t8	10.0	12.0	15.0	ms
t9	10.0	15.0	20.0	ms

Power off



Symbol	SPEC			Unit
	Min	Typ	Max	
t12	10.0	15.0	20.0	ms
t13	5.0	6.0	7.0	ms
t14	10.0	12.0	15.0	ms
t15	20.0	22.0	24.0	ms
t16	1.0	1.5	3.0	ms

PRODUCT GROUP

REV

ISSUE DATE



TFT- LCM PRODUCT

V0

2022-10-11

SPEC. NUMBER  
AM-0700070A

SPEC. TITLE  
FN0700D070A Product Specification


PAGE  
18 OF 28

**6.0 OPTICAL SPECIFICATIONS /光学规格**

Item	Symbol	Condition	Min	Typ.	Max	Unit	Note
Viewing Angle	$\theta_L$	$Cr \geq 10$	60	70	-	deg	Note 1
	$\theta_R$		60	70	-		
	$\psi_T$		50	60	-		
	$\psi_B$		60	70	-		
Contrast Ratio	Cr	$\theta = 0^\circ$	500	800	-	-	Note 2
Response Time	Tr+Tf	FF=0°	--	25	50	ms	Note 3
Color Coordinate of CIE1931	Wx	$\theta = 0^\circ$	0.280	0.310	0.340	-	Note 4
	Wy		0.281	0.311	0.341		
	Rx		0.534	0.564	0.594		
	Ry		0.288	0.318	0.348		
	Gx		0.314	0.344	0.374		
	Gy		0.568	0.598	0.628		
	Bx		0.125	0.155	0.185		
	By		0.042	0.072	0.102		
Uniformity	U		80	--	--	%	Note 5
Color Gamut			41	51	--	%	
Luminance	L		350	400	--	cd/m <sup>2</sup>	Note 6

**Note 1: The definition of Viewing Angle**

Refer to the graph below marked by  $\theta$  and  $\phi$ .



**Note2: The definition of Contrast Ratio**

$$\text{Contrast Ratio(CR)} = \frac{\text{Luminance When LCD is at "White" state}}{\text{Luminance When LCD is at "Black" state}}$$

(Contrast Ratio is measured in optimum common electrode voltage)

**Note3: Definition of Response time.**(Test LCD using RD80S or similar equipments):

The output sign also photo detector are measured when the input sign also are changed from "black" to " white "(Voltage falling time)and from " white " to " black " (Voltage rising time), respectively .The response time is defined as the time interval between the 10% and 90% of amplitudes . Refer to figures below.

**Note 4: Color Coordinates of CIE 1931**

The test condition is at ILED=20mA and measured on the surface of LCD module at 25°C. Measurement equipment: CS2000 or similar equipments  
The Color Coordinate (CIE 1931) is the measurement of the center of the display shown in below figure.

**Note 5: Definition of Luminance Uniformity**

Active area is divided into 9 measuring areas. Every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity (U)} = \text{Lmin/ Lmax}$$


L-----Active area length W----- Active area width

Lmax: The measured Maximum luminance of all measurement position.

Lmin: The measured Minimum luminance of all measurement position.

**Note 6: Definition of Luminance:**

Measure the luminance of white state at center point.



## 7.0 RELIABILITY TEST /可靠性测试

The Reliability test items and its conditions are shown in below.

No	Test Items	Conditions	Testing standard
1	High temperature storage test	80°C 240hr	IEC60068-2-1:2007 GB2423.2-2008
2	Low temperature storage test	-30°C 240hr	
3	Low temperature operation test	-20°C 240hr	
4	High temperature operation test	70°C 240hr	
5	High temperature & humidity (storage test)	60°C 90%RH 240hr	IEC60068-2-78:2001 GB/T2423.3-2006
6	Thermal Shock Test	-30°C~80°C 1hr/cycle 100cycle	Start with cold temperature End with high temperature IEC60068-2-14:1984, GB2423.22-2002
7	Vibration Test	10Hz-55Hz 100m/s <sup>2</sup> 120min	IEC60068-2-32:1990 GB/T2423.8-1995
8	Mechanical shock	100G ±X, ±Y, ±Z, 3times for each direction	
9	Dropping test	Height: 60 cm, 1 corner, 3 edges, 6 surfaces	
10	ESD test	C=150pF, R=330 Ω, 5 points/panel Air:±8KV, 5 times; Contact: ±4KV, 5 times;	IEC61000-4-2:2001 GB/T17626.2-2006 Class C

<b>PRODUCT GROUP</b>	REV	ISSUE DATE	
TFT- LCM PRODUCT	V0	2022-10-11	
SPEC. NUMBER AM-0700070A	SPEC. TITLE FN0700D070A Product Specification		PAGE 21 OF 28

- **8.0 Precautions /注意事项**

- Please pay attention to the followings when you use this TFT LCD Panel.

- **8.1 Mounting Precautions /安装注意事项**

- (1) Use fingerstalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (2) You must mount a module using specified mounting holes (Details refer to the drawings).
- (3) Please make sure to avoid external forces applied to the Source PCB or FPC and D-IC during the process of handling or assembling. If not, It causes panel damage or malfunction.
- (4) Note that polarizers are very fragile and could be easily damaged. Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment.
- (5) Do not pull or fold the source D-IC which connect the source PCB or FPC and the panel.
- Do not pull or fold the LED wire.
- (6) After removing the protective film, when the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with alcohol or purified water.
- Do not strong polar solvent because they cause chemical damage to the polarizer.
- (7) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
- (8) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
- (9) Since the LCD is made of glass, do not apply strong mechanical impact or static load onto it. Handling with care since shock, vibration, and careless handling may seriously affect the product. If it falls from a high place or receives a strong shock, the glass may be broken.
- (10) Do not disassemble the module.
- (11) To determine the optimum mounting angle, refer to the viewing angle range in the specification for each model.
- (12) If the customer's set presses the main parts of the LCD, the LCD may show the abnormal display. But this phenomenon does not mean the malfunction of the LCD and should be pressed by the way of mutual agreement.
- (13) Do not drop water or any chemicals onto the LCD's surface.

<b>PRODUCT GROUP</b>	REV	ISSUE DATE	
TFT- LCM PRODUCT	V0	2022-10-11	
SPEC. NUMBER AM-0700070A	SPEC. TITLE FN0700D070A Product Specification		PAGE 22 OF 28

## 8.2 Operating Precautions /操作注意事项

- (1) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
- (2) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimized the interference.
- (3) The electrochemical reaction caused by DC voltage will lead to LCD degradation, so DC drive should be avoided.
- (4) The LCD modules use C-MOS LSI drivers, so customers are recommended that any unused input terminal would be connected to Vdd or Vss, do not input any signals before power is turn on, and ground you body, work/assembly area, assembly equipments to protect against static electricity.
- (5) Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on) Otherwise the Module may be damaged.
- (6) Design the length of cable to connect between the connector for back-light and the converter as short as possible and the shorter cable shall be connected directly.  
The longer cable between that of back-light and that of converter may cause the luminance of LED to lower and need a higher startup voltage(Vs).
- (7) Connectors are precise devices for connecting PCB and transmitting electrical signals. Operators should insert and unplug MDL in parallel when assembling MDL.
- (8) Do not connect or disconnect the cable to/ from the module at the "Power On" condition.
- (9) When the module is operating, do not lose CLK, ENAB signals. If any one these signals is lost, the LCD panel would be damaged.
- (10) Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.
- (11) Do not re-adjust variable resistor or switch etc.
- (12) For the Q/Single/OC Product, If the LED designed side view, LED bar should be putted in the Long/short side ; Otherwise, its reliability and function may not be guaranteed.

注：  
 ①(1)涉及到Pol相关条目适用于OC/MDL出货产品，  
 ②(6)(7)涉及到connector相关适用于OC/MDL出货产品  
 ③ (12) 涉及到客户进行BLU设计， LED Bar位置需要避开GOA位置；

## 8.3 Electrostatic Discharge Control /静电放电控制

- (1) Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly. Keep products as far away from static electricity as possible.
- (2) Avoid the use work clothing made of synthetic fibers. We recommend cotton clothing or other conductivity-treated fibers.

<b>PRODUCT GROUP</b>		REV	ISSUE DATE	
TFT- LCM PRODUCT		V0	2022-10-11	
SPEC. NUMBER	SPEC. TITLE			PAGE
AM-0700070A	FN0700D070A Product Specification			23 OF 28


#### 8.4 Precautions for Strong Light Exposure / 强光照射注意事项

It is not allowed to store or run directly in strong light or in high temperature and humidity for a long time; Strong light exposure causes degradation of polarizer and color filter.

#### 8.5 Storage Precautions / 存储注意事项

When storing modules as spares for a long time, the following precautions are necessary.

- (1) The polarizer surface should not come in contact with any other object.  
It is recommended that they be stored in the container in which they were shipped.  
Temperature : 5 ~ 40 °C
- (2) Humidity : 35 ~ 75 %RH
- (3) Period : 6 months
- (4) Control of ventilation and temperature is necessary.
- (5) Please make sure to protect the product from strong light exposure, water or moisture.  
Be careful for condensation.
- (6) Store in a polyethylene bag with sealed so as not to enter fresh air outside in it.
- (7) Do not store the LCD near organic solvents or corrosive gasses.
- (8) Please keep the Modules/OC/FOG at a circumstance shown below Fig.



#### 8.6 Precautions for Protection Film / 保护膜注意事项

- (1) Remove the protective film slowly, keeping the removing direction approximate 30-degree not vertical from panel surface, If possible, under ESD control device like ion blower, and the humidity of working room should be kept over 50%RH to reduce the risk of static charge.
- (2) In handling the LCD, wear non-charged material gloves. And the conducting wrist to the earth and the conducting shoes to the earth are necessary.

#### 8.7 Appropriate Condition for Display / 适当的显示条件

- (1) Normal operating condition
  - Temperature: 0 ~ 40°C
  - Operating Ambient Humidity : 10 ~ 90 %
  - Display pattern: dynamic pattern (Real display)
  - Suitable operating time: under 12 hours a day.
- (2) Special operating condition  
If the product will be used in extreme conditions such as high temperature, humidity, display patterns or 7\*24hrs operation time etc., It is strongly recommended to contact us for Application engineering advice. Otherwise, its reliability and function may not be guaranteed.
- (3) Black image or moving image is strongly recommended as a screen save.

<b>PRODUCT GROUP</b>	REV	ISSUE DATE	
TFT- LCM PRODUCT	V0	2022-10-11	
SPEC. NUMBER AM-0700070A	SPEC. TITLE FN0700D070A Product Specification		PAGE 24 OF 28

- (4) Lifetime in this spec. is guaranteed only when commercial display is used according to operating usages.
- (5) Please contact us in advance when you display the same pattern for a long time.
- (6) If the Module keeps displaying the same pattern for a long period of time, the image may be “sticked“ or “turn off” to the screen. To avoid image sticking, it is recommended to use a screen saver.
- (7) Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on) Otherwise the Module may be damaged.
- (8) Dew drop atmosphere should be avoided.
- (9) The storage room should be equipped with a good ventilation facility and avoid to expose to corrosive gas , which has a temperature controlling system.
- (10) The LCD should be avoided to expose to corrosive gas for long time, ,the LCD may be affected by the gas as SO<sub>2</sub> ,H<sub>2</sub>S etc.
- (11) When expose to drastic fluctuation of temperature (hot to cold or cold to hot) ,the LCD may be affected; Specifically, drastic temperature fluctuation from cold to hot ,produces dew on the LCD's surface which may affect the operation of the polarizer and the LCD.
- (12) Response time will be extremely delayed at lower temperature than the operating temperature range and on the other hand at higher temperature LCD may turn black at temperature above its operational range. However those phenomena do not mean malfunction or out of order with the LCD. The LCD will revert to normal operation once the temperature returns to the recommended temperature range for normal operation

## 8.8 Others /其他

### A. LC Leak /液晶泄露

- If the liquid crystal material leaks from the panel, it is recommended to wash the LC with acetone or ethanol and then burn it.
- In case of contact with hands, skin or clothes, it has to be washed away thoroughly with soap.
- If LC in mouth, mouth need to be washed, drink plenty of water to induce vomiting and follow medical advice.
- If LC touch eyes, eyes need to be washed with running water at least 15 minutes.

### B. Rework /返工

- When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

- C. In order to prevent potential problems, flicker should be adjusted by optimizing the Vcom value in customer LCM Line (适用于Q/Single/OC出货产品)

PRODUCT GROUP

REV

ISSUE DATE



TFT- LCM PRODUCT

V0

2022-10-11

SPEC. NUMBER  
AM-0700070A

SPEC. TITLE  
FN0700D070A Product Specification

PAGE  
25 OF 28

### 9.0 PACKING INFORMATION(产品形态: LCM )

LCM MODEL	LCM Qty. in the Box	Carton Size(mm)	LCM Qty. in the Pallet
FN0700D070A	80pcs/BOX	530*360*275mm	1600pcs/Pallet




PE BAG包折到Panel面

PE BAG: FHXXXXXXXXXX001A




EPE: FN070AM01-ZZ-V5.0




2片叠放, Panel对立



BOX: FN070AM01-ZX-V1.0



FN070AM01-MT



## 10.0 VISUAL INSPECTION CRITERIA FOR ALL CUSTOMERS /所有客户的目视检查标准

### 10.1 Sampling Method /抽样方法

Unless otherwise agreed upon in writing, the sampling inspection shall be applied to the Customers incoming inspection.

- 10.1.1 Lot size : 1 pallet per same model
- 10.1.2 Sampling type : Random sampling
- 10.1.3 Inspection level : II
- 10.1.4 Sampling table : MIL-STD-105E

### 10.2 Inspection Environment /检验环境

#### 10.2.1 Ambient conditions

- a. Ambient Temperature:  $25 \pm 3^{\circ}\text{C}$
- b. Relative Humidity:  $65 \pm 20\% \text{RH}$
- c. Ambient Illumination: 300-700LUX (Normal: 500LUX)

#### 10.2.2 Viewing Distance

The distance between the LCM and the inspector's eyes shall be at least 30cm-50cm

#### 10.2.3 Viewing Angle


performing in front of the panel

[Vertical] :  $\pm 25^{\circ}$

[Horizontal] :  $\pm 40^{\circ}$

#### 10.2.4 Inspection Area:

Display Area (Active Area)



### 10.3 Definitions /定义

#### 10.3.1 Dark / Bright Spots

Points on display which appear dark/bright and usually result from the contamination.

These defects do not vary in size or intensity (contrast) when contrast is varied.

#### 10.3.2 Dark / Bright Lines

Lines on display which appear dark/bright and usually result from the contamination.

#### 10.3.3 Polarizer Scratch

Lines on display which are seen across a darker background and do not vary in size.

#### 10.3.4 Polarizer Dent

White spots on display which appear against a darker background and do not vary in size.

#### 10.3.5 Bright Dot Defects

Dots (sub-pixels) on display which appear bright in the display area and visible through the 5%ND filter at Black Pattern.

<b>PRODUCT GROUP</b>	REV	ISSUE DATE	
TFT- LCM PRODUCT	V0	2022-10-11	
SPEC. NUMBER AM-0700070A	SPEC. TITLE FN0700D070A Product Specification		PAGE 27 OF 28

#### 10.3.6 Dark Dot Defects

Dots(sub-pixels)on display which appear dark in the display area at R.G.B Color Pattern.

#### 10.3.7 Line Defects

All line defects on display which appear bright/dark such as vertical, horizontal, or cross lines.

#### 10.3.8 Mura

Mura on display which appears darker/brighter against background brightness on parts of display area.

#### 10.3.9 BM Defects

Bright(white)Points on display which are off BM(Black Matrix).

#### 10.3.10 Visual Inspection

Inspection for LCM when the unit turns on.

#### 10.3.11 Appearance Inspection

External inspection for LCM when the unit turns off.

#### 10.3.12 Other

Defects which cannot be classified into the above defect definitions.

Note 1: Bright& Dark dots are not smaller than a sub-pixel(Dots smaller than a sub-pixel are not counted as defect dots)

### 10.4 Inspectin Criteria /检验标准

Refer to 《TFT LCM general inspection standard》

### 10.5 Verification /验证

The supplier can verify the defective LCMs to segregate the responsibilities at customer's facility or can request the Customer to ship the defective LCMs to assigned place for verification

This verification result shall be agreed mutually by the Customer and Supplier. This result can be corrected/changed after detail failure analysis at Supplier's facilities.

### 10.6 Supplier Induced Defects /供应商引起的缺陷

All of the Supplier induced defective LCMs shall be returned to the Supplier for repair or replacement.

Before return the defective LCMs, the Customer needs Supplier's confirmation with RMA Number.

All of the returned LCMs shall be returned to the Customer within agreed time period.

<b>PRODUCT GROUP</b>	REV	ISSUE DATE	
TFT- LCM PRODUCT	V0	2022-10-11	
SPEC. NUMBER AM-0700070A	SPEC. TITLE FN0700D070A Product Specification		PAGE 28 OF 28

### 10.7 Customer Induced Defects /顾客引起的缺陷

The Customer can return the customer induced defective LCMs to the Supplier for repair. The repair cost for Customer induced defective LCMs shall be agreed with both parties, Customer and Supplier.

### 10.8 Warranty Period /质量保证期

In-warranty period is Eighteen(18)Months from manufacturing month of LCM

Note :

- a. Eighteen months are composed of twelfth months in-warranty period and sixth months distribution period
- b. The manufacturing Month is on the LCMs as Supplier's serial No.

### 10.9 Repair Warranty /维修保证书

Repair warranty is Twelve(12)Months from repaired month for repaired LCMs

Note : a. The Label for repair will be added after repairing.

### 10.10 Warranty avoidance /避免担保

The warranty will be avoided in cases of below:

- a. When the warranty period is expired.
- b. The Customer induced defective LCMs.
- c. When the LCMs were repaired by 3rd party without Supplier's approval.
- d. When the LCMs were treated like Disassemble and Rework by the Customer and/or Customer's representatives without Supplier's approval.

### 10.11 Others /其他

If any problems arise with the LCMs supplied by supplier, the customer and supplier will cooperate and make efforts to solve it with mutual confidence and respect